

LCD Monitor L7VH-TS Vista Clear Series

- Product Specification -

Configuration	L7VH-TS		
LCD Display	17.0" TFT active matrix panel		
Display Size	337.9(H)x270.3(V) mm		
Pixel Pitch	0.264(H)x0.264(V) mm		
Max. Resolution	SXGA 1280x1024		
Contrast Ratio	350:1 (typical)		
Brightness	250 cd/m ² (typical)		
Response Time	20 ms		
Display Color	16M		
Viewing Angle	L/R	+80°~-80° = 160 total range	
	U/D	+80°~-80° = 160 total range	
PC Interface	Video	RGB analog 0.7V peak to peak	
	Sync.	TTL positive or negative	
	Display Mode		VGA 720x400 (70 Hz)
			VGA 640x480 (60/70/72/75 Hz)
			SVGA 800x600 (56/60/72/75 Hz)
			XGA 1024x768 (60/70/75 Hz)
	SXGA 1280x1024 (60/75 Hz)		
	Input Connector	D-sub 15 pin	
Video Interface Optional Module	Video Input	Composite (CVBS) Video; Y/C Separated	
	Input Connector	RCA for CVBS	
		4-Pins S Terminal for Y/C	
TV Tuner Optional Module	Receiving Channel	181 MTS CH (113 CATV)	
	Input Connector	F type Jack	
	Audio Output	3.5 mm Mini Stereo Connector	
Audio Interface	Amplify	Building Internal Audio Amplify	
	Input Connector	3.5 mm Mini Stereo Connector	
	Speaker	2W / per channel driver	
Front Control	Power on/off with LED, Menu, Select, Adjustment (+,-)		
Remote Control	32 Keys Full Function Remote Control		
PIP (Picture in Picture)	Video on PC mode .or. TV on PC mode		
Plug & Play	DDC1/2B compatible		
Power Adapter	Input AC 90~264V, 50~60Hz; Output DC 12V / 3.5A		
Operating Conditions	Temperature	5°C-35°C (41°F-95°F)	
	Humidity	20%-80% (no condensation)	
	Altitude	To 10,000 feet	
Storage Conditions	Temperature	-20°C-60°C (-4°F-140°F)	
	Humidity	10%-90% (no condensation)	
Optional Module	Adjustable Arm		
Certification	C-UL, FCC, CE, TUV/GS, BSMI, EPA, NUTEK, TCO		

* Specifications are subject to change without notice.

Rev. 0.0

